

FEATURES

- 4 U high-density storage server supports 60 hot swap 3.5” SAS drive bays
- Supports 3rd generation Intel® Xeon® Scalable Processor (Ice Lake)
- Intel® C621A chipset
- Supports 16 DDR4 DIMM slots for maximum memory performance upto 4TB
- Onboard Baseboard Management Controller for system management and IPMI control, Dedicated BMC management port
- Front-to-back airflow and hot swap redundant fans to provide optimal thermal conditions
- Trusted Platform Module 2.0 onboard.
- Supports 800W 2+2 redundant power supply 80+ Platinum.

SPECIFICATIONS			
Model Number	InfiniPlus HD4260-i3		
Processor	Support	3 rd Gen Intel Xeon Scalable Processors (Ice Lake) CPU TDP: 270W	
	Socket Type	Socket P+ (LGA-4189)	
Chipset	Intel® C621A Chipset		
System Memory & Max Capacity	<ul style="list-style-type: none"> • 8 x Memory channels per CPU • 16 x DIMM slots support: DDR4 3200/2933MHz RDIMM/LRDIMM • Up to 4094GB LRDIMM/RDIMM 		
Front Panel	<ul style="list-style-type: none"> • System Power on/off • System reset • System ID • 2 x USB 3.0 ports 		
LED	<ul style="list-style-type: none"> • Power status • System alert • Lan activity • Drive activity • System ID 		
Drive Bays	Top-load	3.5"/2.5" hot swap	60 (SATA/SAS)
	Rear panel	2.5" hot swap	8 NVMe / 2 x SATA (optional)
	Internal	M.2	2 x M.2(NGFF)/M-Key/2280
Backplane	<ul style="list-style-type: none"> • 2 x 30-port 12G SAS backplanes with 40-PHY expander OR <ul style="list-style-type: none"> • 2 x 30-port 24G SAS backplanes with 40-PHY expander 		
Expansion Slots	PCI 4.0:	<ul style="list-style-type: none"> • 3 x PCIe x16 slots + 1 x OCP 3.0 • 2 x PCIe x8 slots 	
Graphics	A speed AST2500 Advanced PCIe Graphics & Remote Management Processor <ul style="list-style-type: none"> • PCIe VGA/2D Controller • 1920x1200@60Hz 32bpp 		
Rear Ports	Network Controllers	1 x GbE RJ45 Realtek RTL8211E GbE for BMC dedicated management port 1 x GbE RJ45 Intel I210 GbE for BMC shared NIC management port by onboard connector	
	USB	2 x USB 3.0	
	Video Output	1 x external DB-15 VGA port	
	Serial Port	1 x external COM port jack	
Power Supply	800W 2+2 redundant PSU 80+Platinum AC INPUT: 100~240V,50/60Hz,10-5A		
System Cooling	4 x 80x38mm hot swap fans With ABS Air Duct		
Environmental	Storage temperature: -10°C(14°F) ~ 60°C(140°F)		

Specifications	Operating temperature: 0°C(32°F) ~ 35°C(95°F) Storage operating humidity: 5%~95% non-condensing	
System Management	<ul style="list-style-type: none"> • IPMI: Advanced PCIe Graphics & Remote Management Processor • Baseboard Management Controller • Intelligent Platform Interface 2.0 (IPMI 2.0) • iKVM, Media Redirection, IPMI over LAN, Serial over LAN • SMASH Support 	
Gross Weight	(w/ PSU & Rail)	Kg: 80
Dimensions	(W x D x H)	mm: 434 x 853 x 176
		inches: 17.1 x 33.5 x 6.9
Certification	BIS, RoHS compliant	
Warranty	3 Years +2 Years Extended	
Additional Accessories	<ul style="list-style-type: none"> • HBA (FC iSCSI & SAS) & Raid - OCP3.0/ PCIe 4.0 x8 • Dual Port 1GbE RJ45 Network Card • Dual Port 10 GbE RJ45 Network card • Dual-Port 10G SFP+ OCP 3.0/ PCIe 4.0 x8 • Dual Port QSFP 25GbE Ethernet Network Adapter • QUAD PORT 10GbE SFP+ Ethernet Network Adapter • Quad-Port 16 GB FC Adapter • Dual Port 25 Gb/s Network Interface Card • Quad Port 25Gbs Network Interface Card • CDAT Dual port 100Gbs PCIe 4.0 x16 • Dual 40 GbE QSFP+ Direct Attach Cabling up to 10m 	
Mounting	Standard 28" tool-less slide rail	